

Technical data sheet Pipe-Seal-End

Pipe-Seal sleeve DN	Rubber seal DN	Sleeve length	Stainless steel sleeve		Suitable for pipes		Liner cutback	Sheet thickness	EPDM rubber seal			Liner thickness	
			Roll dimension	Max. tensioning dimension	Min. pipe interior (liner) diameter	Max. pipe interior diameter (without compression)			Rubber surface thickness	Rubber thickness incl. seal knobs, liner	Rubber thickness incl. seal knobs, old pipe	Min.	Max.
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
150	150	250	119	149	131	169	100-140	1	2	6	12	3	10
188	188	250	151	188	163	208	100-140	1,25	2	6	12	3	10
200	200	250	160,5	201	173	221	100-140	1,25	2	6	12	3	10
210	200	250	170	212	182	232	100-140	1,25	2	6	12	3	10
225	225	250	182	227	194	247	100-140	1,25	2	6	12	3	10
240	240	250	194	242	206	262	100-140	1,25	2	6	12	3	10
250	250	250	202	252	214	272	100-140	1,25	2	6	12	3	10
276	276	250	220	278	232	298	100-140	1,25	2	6	12	3	10
286	286	250	229	288	241	308	100-140	1,25	2	6	12	3	10
300	300	250	243	305	255	325	100-140	1,25	2	6	12	3	10
315	315	250	253	315	265	335	100-140	1,25	2	6	12	3	10
330	330	250	270	335	282	355	100-140	1,25	2	6	12	3	10
350	350	250	290	355	302	375	100-140	1,5	2	6	12	3	10
380	380	250	300	377	312	397	100-140	1,5	2	6	12	3	10
400	400	250	327	408	339	428	100-140	1,5	2	6	12	3	10
450	450	250	374	456	386	476	100-140	1,5	2	6	12	3	10
480	480	250	388	480	400	500	100-140	1,5	2	6	12	3	10
500	500	250	424	506	436	526	100-140	1,5	2	6	12	3	10
530	530	250	448	530	460	550	100-140	1,5	2	6	12	3	10
580	580	300	455	580	467	600	120-160	2	2	6	12	3	12
600	600	300	515	609	527	629	120-160	2	2	6	12	3	12
650	650	300	560	659	572	679	120-160	2	2	6	12	3	12
700	700	300	560	713	572	733	120-160	2	2	6	12	3	12
750	750	300	595	758	607	778	120-160	2	2	6	12	3	12
800	800	300	697	814	709	834	120-160	2	2	6	12	3	12

Note

1. Always install the smaller flanged edge in the direction of the liner, and the larger flanged edge in the direction of the old pipe.
2. It is no longer possible to insert the Pipe-Seal-End bigger than DN 750 through the manhole cone!